



## Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 x lamp 1 x fixing elements
Power factor	0.9

## Complementary

Outlet standard	French
Rated lamp wattage	10 W
[Ue] rated operational voltage	230 V AC - 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-in switch
Luminous flux	640 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m not supplied Cable quick connector 1 m not supplied
Mounting support	DIN rail Metal parts Bracket
Fixing mode	Magnetic fixing Clip-in Screws
Range compatibility	Spacial Thalassa
Material	PC (UL94 V-0)

Length	372 mm
Height	63 mm
Width	40 mm
Colour	Black RAL 9005

## Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Electromagnetic compatibility	EMC immunity conforming to EN 55015
Standards	UL 8750 UL 94 UL 1598 UL 508 A EN 55015 IEC 60598
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

## Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold