

Laser marker - TOPMARK NEO - 1012015

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Laser marker, Includes operating instructions, declaration of conformity, LS adapter plate, type E and F power cables, LAN cable, weight: 47 kg, width: 580 mm, height: 615 mm

Your advantages

- Maintenance-free operation, thanks to fiber laser technology
- Intuitive and time-saving operation using integrated marking software with a graphical user interface
- Minimal installation space: surface of only approx. two DIN-A3 sheets is required
- Rapid marking of plastic and metal plates for marking terminals, conductors, cables, devices, and plant marking
- Laser class 1 in accordance with DIN EN 60825-1: no laser operative required
- For all UniCard (UCT) and LaserSheet (LS) materials
- High-quality, fast marking. Marking a UniCard in just 8 seconds



Key Commercial Data

Packing unit	1 pc
GTIN	4 055626 487922
GTIN	4055626487922

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

General

Interface	Ethernet 10/100 Mbps, dynamic IP/RS-232/USB host for USB stick
Weight	47 kg
Laser system	Ytterbium fiber laser, pulsed, 1064 nm
Laser class	Laser class 1 according to EN 60825-1 classification



Laser marker - TOPMARK NEO - 1012015

Technical data

CW laser power

\sim	
I - Or	nerai
Ger	nerai

Length	485 mm
Height	615 mm
Width	580 mm
Connection data	
Minimum voltage	100 V AC
Max. voltage	240 V AC
Additional text	50 Hz 60 Hz
Standards and Regulations	
Laser class	Laser class 1 according to EN 60825-1 classification
Environmental Product Compliance	
REACh SVHC	Lead 7439-92-1

20 W

Ex Approvals

Approvals

EAC

Approval details

EAC [H[

RU D-DE.BL08.B.03051

Phoenix Contact 2019 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com