

Laser marker - TOPMARK NEO SET - 1012018

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Laser marker incl. extraction unit, includes operating instructions, declaration of conformity, LS adapter plate, type E and F power cables, LAN cable, D-SUB cable 25-pos., suction tube, crevice nozzle set and filter equipment

Your advantages

- Maintenance-free operation, thanks to fiber laser technology
- Intuitive and time-saving operation using integrated marking software with a graphical user interface
- Minimal installation space: surface of only approx. two DIN-A3 sheets is required
- Rapid marking of plastic and metal plates for marking terminals, conductors, cables, devices, and plant marking
- Laser class 1 in accordance with DIN EN 60825-1: no laser operative required
- For all UniCard (UCT) and LaserSheet (LS) materials
- High-quality, fast marking. Marking a UniCard in just 8 seconds



Key Commercial Data

| Packing unit | 1 pc |
|--------------|-----------------|
| GTIN | 4 055626 486284 |
| GTIN | 4055626486284 |

Technical data

General

| Interface | Ethernet 10/100 Mbps, dynamic IP/RS-232/USB host for USB stick |
|----------------|--|
| Weight | 102 kg |
| Laser system | Ytterbium fiber laser, pulsed, 1064 nm |
| Laser class | Laser class 1 according to EN 60825-1 classification |
| CW laser power | 20 W |

Connection data

| Minimum voltage | 100 V AC |
|-----------------|----------|



Laser marker - TOPMARK NEO SET - 1012018

Technical data

Connection data

| Max. voltage | 240 V AC |
|-----------------|-------------|
| Additional text | 50 Hz 60 Hz |

Standards and Regulations

| Laser class 1 according to EN 60825-1 classification |
|--|
|--|

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC

RU D-DE.BL08.B.03051

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com