

Fiber optic - HS LC-H-D2C/ R2XC1-2,54 - 1036658

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Light guides, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)

Your advantages

- ✓ Light guides are perfectly matched to electronics housings
- ✓ Easy mounting on the PCB using press pins
- ✓ Resistance to ESD
- ✓ Housing processing available on request



Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 055626 541884
GTIN	4055626541884

Technical data

Product properties

Brief article description	Fiber optic
Type	HS LC-H-D2C/ R2XC1-2,54
Order No.	1036658
Type	passive, rigid
Alignment	Horizontal
Number of displays	2 (2 rows x 1 column)
ESD protection	< 8 kV
Head form	Round, conical

Dimensions

Pitch	2.54 mm
Diameter	2 mm

Fiber optic - HS LC-H-D2C/ R2XC1-2,54 - 1036658

Technical data

Dimensions

Hole diameter	1.2 mm
---------------	--------

Material specifications

Material	PC
Color (RAL)	transparent
	black (9005)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General information

Type of note	Assembly instruction:
Note	Refer to the data sheet for the range in the download area.
	The tops of the press-in pegs are conical to make installation easier.
	To prevent glare, the system has an aperture. This also makes mixed colors possible.

Packaging details

Pieces per package	100
Denomination packing units	Pcs.

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>