

## Fiber optic coupling - FOC-I-D1PGY-S/MPBGC - 1041840

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fiber optic coupling, degree of protection: IP20, connection method: Coupling, cable outlet: straight

### Your advantages

- Assembly without special tools
- Flexible use, thanks to DIN rail and direct mounting
- Space-saving design
- With dust protection caps

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 598680
GTIN	4055626598680

### Technical data

#### Mechanical characteristics

Number of slots	1
Connection profile	MTP: type B
Connection method	Coupling
Cable outlet	straight
Mounting type	Snap in
Degree of protection	IP20
No. of cable outlets	2
Type of note	Notes on operation
Note	For integration into DIN rail adapter NBC-PP-G1PGY

#### Ambient conditions

Ambient temperature (operation)	-10 °C ... 70 °C
Degree of protection	IP20

## Fiber optic coupling - FOC-I-D1PGY-S/MPBGC - 1041840

### Technical data

#### Material data

Flammability rating according to UL 94	V0
--	----

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>