

Connection plate - ICS25-F45S-7035 - 2203891

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

ICS-Filler, closed, width: 25 mm, color: light gray (7035)



Your advantages

- ✓ Flexible use, thanks to the modular system and unique modularity in the connection technology
- ✓ Standardized connections such as RJ45, USB, D-SUB, and antenna sockets as integrative components
- ✓ Optimal space utilization as well as adaptability of design, colors, and printing
- ✓ 8-position DIN rail connector for easy module-to-module communication

RoHS

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 055626 465968
GTIN	4055626465968

Technical data

Item properties

Brief article description	Connection plate
Type	ICS25-F45S-7035
Order No.	2203891
Housing type	ICS-Filler
Type	closed

Dimensions

Width [w]	25 mm
Height [h]	7 mm
Depth [d]	45 mm

Material data

Connection plate - ICS25-F45S-7035 - 2203891

Technical data

Material data

Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0
Housing material	PA 6.6

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 100 °C (observe derating)

Packaging information

Pieces per package	10
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	---	---	---------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>