

Battery - STEP-BAT/LI-ION/18.5DC/46WH - 1081355

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Replacement battery module, lithium-ion, 18.5 V DC, 46 Wh



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626809427

Technical data

Dimensions

Width	88 mm
Height	46 mm
Depth	61 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 45 °C
Max. permissible relative humidity (operation)	≤ 95 % (25 °C, non-condensing)
Degree of pollution	2

Input data

Nominal input voltage	18.5 V DC
-----------------------	-----------

Output data

Balancer circuit, internal	yes
Protective circuit, internal	yes

General

IQ technology	no
---------------	----

Battery - STEP-BAT/LI-ION/18.5DC/46WH - 1081355

Technical data

General

Net weight	0.28 kg
Memory medium	Lithium-ion, 46 Wh
Protection class	III
Degree of protection	IP20

Charging process

Charge current	400 mA
End-of-charge voltage	21 V DC

Approvals

Approvals

Approvals

IECEE CB Scheme / cULus Recognized / cULus Recognized

Ex Approvals

Approval details

IECEE CB Scheme		http://www.iecee.org/	DK-85769-UL
-----------------	--	---	-------------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	MH48963
------------------	--	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	MH48963
------------------	--	---	---------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>