





Mechanical characteristics

interface dimensions acc. to housing

Mechanische Eigenschaften

Steckgesicht nach Gehäuse

IEC 61169-54
material - aluminium
colour/Farbe - silver/silber

Electrical characteristics

impedance
frequency
return loss
intermodulation
power

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Rückflussdämpfung
Intermodulation
Leistung

50 Ω
650 - 3000 MHz
 ≥ 23 dB
(a) typ. ≤ -161 dBc @ 2x43 dBm
30 W


Environmental

operating temp.
RoHS compliant
warning:
hot heat sink

Umgebung

Betriebstemperatur
RoHS konform
Warnung:
Heißer Kühlkörper

-35°C / +55°C
2011/65/EU

Änd./ rev. Index	Änderungs-Nr. / revision code	Datum/ date	Name/ name		Datum/ date	Name/ name	Gewicht/ weight [g]			
a	31010	21.01.2020	MA	gez./ drawn	14.08.2019	KL	ca./approx. 653			
				gepr./ appr.	11.09.2019	GB				
				Maßstab/ scale 1:1 (1:2)	Benennung/ title 4.3-10 Low PIM Load (m) 4.3-10 Abschlusswiderstand (m)				 Telegärtner	
				untl. Maße/ dim. without tolerances according to	Untert./ doc. type K	Zeichnungsnr./ drawing no. J01444A0003				 Maße/ dimensions: mm
Ersatz für/ replaces				Original : DIN A4						
								Blatt/ sheet 1 von/ of 1		