



VARDAflex Plus DTW - 5-Meter-Rolle


Flex. LED-Strip, 24V, 7, 5W/m, Innen, DTW CRI80

Article nr.: PGI141

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 100 mm / 12 LEDs teilbar ·
Anzahl der LEDs: 600 · LED Abstand: 16,67 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro
Meter: 772 lm · Lichtfarbe: 3300 K - 1900 K (Dim To Warm) · Betriebsspannung: 24 V DC · Leistung
pro Meter: 7,5 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000
x 10 x 1,5 · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. ·
Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4251835891417
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	3300-1900K Dim to Warm
Lightoutput per fixture	3860.00 lm
Lightoutput per LED	6.43 lm
Lamp	Inklusive LED





VARDAflex Plus DTW - 5-Meter-Rolle

Flex. LED-Strip, 24V, 7, 5W/m, Innen, DTW CRI80

Article nr.: PGI141

TECHNICAL DATA

IP rating	20
Power	37,5 W
Psb	0,00 W
Current mA	1.563 mA
Voltage	24 V
Amount of LED	600
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h





VARDAflex Plus DTW - 5-Meter-Rolle
Flex. LED-Strip, 24V, 7, 5W/m, Innen,
DTW CRI80

Article nr.: PGI141

TECHNICAL DRAWING

