

BIS Stockschrauben (ev)

(K 40 05)

Befestigung an Wand oder Decke



Vorteile und Eigenschaften

- Sechskant für Feinjustierung
- Material: Stahl
- elektrolytisch verzinkt

Art.Nr.	G	L	Lh (mm)	Lm1 (mm)	PØ (mm)	SW1 (mm)	Tx	VPE 1	VPE 2	Gew / 1 Einh (g)
6263606	M6	60 mm	35	25	8	-	-	100	1.000	10.00
6263609	M6	90 mm	30	30	8	5	-	100	1.000	16.00
6263612	M6	120 mm	30	30	8	5	-	100	1.000	19.90
6263615	M6	150 mm	30	45	8	5	-	100	1.000	24.90
6263805	M8	50 mm	35	15	10	6	25	100	1.000	10.80
6263806	M8	60 mm	30	20	10	6	25	100	1.000	15.80
6263808	M8	80 mm	35	35	10	6	25	100	1.000	19.23
6263810	M8	100 mm	50	40	10	6	25	100	500	24.00
6263812	M8	120 mm	50	40	10	6	25	100	500	30.30
6263815	M8	150 mm	50	50	10	6	25	50	500	36.00
6263816	M8	160 mm	60	40	10	6	25	50	250	44.00
6263818	M8	180 mm	60	40	10	6	25	50	250	48.00
6263820	M8	200 mm	50	50	10	6	25	50	250	54.50
6283006	M10	60 mm	35	15	12	8	25	50	500	20.00
6283008	M10	80 mm	35	35	12	8	25	50	500	26.00
6283010	M10	100 mm	50	40	12	8	25	50	500	38.50
6283011	M10	110 mm	50	40	12	8	25	50	500	44.00
6283012	M10	120 mm	50	40	12	8	25	50	500	50.00
6283014	M10	140 mm	50	40	12	8	25	50	250	58.00
6283018	M10	180 mm	55	60	12	8	25	50	250	78.00
6283020	M10	200 mm	55	40	12	8	25	50	250	92.00
6283210	M12	100 mm	50	30	12	10	30	50	250	53.00
6283212	M12	120 mm	60	45	12	10	30	50	250	77.00
6283214	M12	140 mm	60	60	12	10	30	50	250	79.50

